

WE SENSE DISASTER...
AND NOW YOU ARE IN CONTROL...



Sensor Controlled Relay

The **Sensor Controlled Relay** controls the electrical power to devices over the Internet. With easy configuration & integration with sensorProbe product series, It defines a new era in energy management.

The **Sensor Controlled Relay** provides 1 high-power SPDT 5V relay. It includes Metal Oxide Varistors (MOVs) and Snubber circuits to protect the open contact of the relays from the high voltage spikes or noise transients. It monitors the power & load and accepts a control signal which is sent from the sensorProbe.

Specifications

Input Voltage	110 - 220 VAC
Output Voltage	110 - 220 VAC
Relay	
- Contact Rating	10 Amps for 220VAC and 10 Amps for 110VAC Power cords supplied support a maximum of 6 Amps
- Contact Material	AgCdO
- Carry Current	10 Amps
- Max Operating Voltage	380 VAC ,125 VDC
- Max Operating Current	10 Amps
Max Switching Capacity	4000 VA, 480W with Resistive Load 2000 VA, 240W with Inductive Load(P.F=0.4)
Min Permissible Load	100mA 5 VDC
Power Consumption	Typical 471.00 mWatt, 94.20mA
PCB Copper Track Rating	10 Amps
10 Amps Fuse	380 VAC, 125 VDC
Dimensions	115(w) x 80(H) x 40(D) mm
Operating Temperature	-40 C to 85 C
Storage Temperature	-40 C to 85 C
Weight	250 gms



Features

- IEC connector rating is 10 Amps for 220VAC and 10 Amps for 110VAC
- Power cords supplied support maximum 6A
- Metal Oxide Varistors (MOVs) and snubber circuit protect the open contacts of the relays from high voltage spike.
- 4 LEDs indicate the status of the Relay, Power Supply, AC Line Voltage and AC Load Voltage.
- Up to two Power Relay Boards per sensorProbe2, up to 8 per sensorProbe8 and cameraProbe8
- Full auto sense including disconnect alarm.
- PRB00-110 and PRB00-220 can be extended to your desired cable length using one of our CAT5 extension cables, CABXX, or you can provide your own cable of any length up to 100 feet.